

K2 S3L FO CI SR

3C149E

CE EN ISO 20345:2022 S3L FO CI SR

High safety shoe, anti-scratch back leather WPA thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Reinforced heel area STABILITY SUPPORT in PU.

Shoe with refracting fabric insert. Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

PL MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE 3CROSS three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping

ANTITORSION insert in the sole to assure stability on uneven ground

INSOLE MEMORY, three-materials extracomfort insole with soft latex Memory no-stress in the heel zone and in the bending point, resistant to the body pressure. Perspiring, removable, anatomic, absorbing, antistatic and antibacterial.

FO sole resistance to hydrocarbons

CI insulating bottom against cold -17 °F C

SR Resistance to slipping

Size 39-47 Shoe weight Sz 42 gr. 585






CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 FARMING AND MINING  COMPONENTS AND AUTOMOTIVE  WOOD METAL CARPENTRY  BUILDING AND HEAVY INDUSTRY  LOGISTICS AND LIGHT INDUSTRY  OIL AND GAS

SOLE




3Cross is a square-shaped, **dynamic** and vibrant footwear. This has been designed for those working **outdoors** on **irregular surfaces**.

3Cross belongs to the **3D generation**. This shoe therefore has **3 different PU injected layers** with relative densities, each specialized to maximize comfort, anti-slip and foot stability.

Some of these models are also equipped with an **antitorsion** insert to guarantee further support to the foot at every step.

ANTISLIPPING TEST RESULTS		
	request	results
ceramic + NaLS	HEEL ≥ = 0,28	0,33
	FLAT ≥ = 0,32	0,32
	HEEL ≥ = 0,13	0,25
	FLAT ≥ = 0,18	0,25



SRA+SRB=

SRC
ANTI-SLIPPING SOLE

PLUS



ANTI TORSION

The usage of the anti-torsion shank is finalized to give to the shoe extreme stability on every ground. Mostly indicated for the building sector, where the risks caused by uneven and wet grounds are higher, this technology is very useful for people working on ladders (painters, windows' cleaners, bricklayers) as it increases the stability in the centrla part of the plant, the mostly standed area on the ladder. It limits the heel stress and helps plant arch and ankle.



ZERO ABRASION

The Zero Abrasion technology is an anti-scratch leather, finished with a plyurethane multi-layer, that assures a complete protection of the upper against usury and abrasion. Highly resistant to water and oils, this leather is suitable for people who like wearing always clean and nice shoes even after months of usage.



STABILITY SUPPORT

Stability Support is the Giasco technology the guarantees the maximum heel support during walking. Inside it there's a particular structure that localizes the support only on specific areas, in order to avoid an excessive stress of the foot. It helps the correct walking and a better discharge of the weight along all the foot, with advantaged for back and joints.



3D TRIPLA DENSITA' INIETTATA

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.



MEMORY FOAM INSOLE

The MEMORY FOAM insole guarantees an excellent comfort thanks to the innovative material of which it is made, which allows it to adapt to the shape of the foot. This, in addition to making walking more pleasant, supports posture, improves the fit of the shoe and distributes the body weight better. Moreover, this stabilizes the foot and reduces the impact with the ground, absorbing shocks and guaranteeing an excellent shock absorber.