

PERU S1PL FO SR

KU095T

CE UNI EN ISO 20345:2012 S1P SRC ESD

Safety Sandal, suede leather thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Closing with strap.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN 22568

PL MIDSOLE flexible antiperforation composite fabric according to EN 22568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000 three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**.

FO sole resistance to hydrocarbons

SR sole resistance against slipping



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 COMPONENTS AND AUTOMOTIVE  WOOD METAL CARPENTRY 
LOGISTICS AND LIGHT INDUSTRY  ESD AREAS

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an **excellent anti-slipping product**.

This sole is called **Kube**, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole.

With thanks to these special characteristics Kube obtained the maximum certification against slipping: **jobs on inclined roofs** (UNI 11583:2015).

ANTISLIPPING
TEST RESULTS

	request	results
SRA		
ceramic +	HEEL \geq = 0,28	0,37
NaLS	FLAT \geq = 0,32	0,39
SRB		
steel +	HEEL \geq = 0,13	0,20
glycerol	FLAT \geq = 0,18	0,30

