

KAYAK S3

KU025T

CE UNI EN ISO 20345:2012 S3 SRC ESD

Low safety shoe, suede back leather WRU thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC INSOLE 5000, three-materials extracomfort**: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial
The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 36-47 Shoe weight Sz 42 gr. 550



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS

 COMPONENTS AND AUTOMOTIVE  WOOD METAL CARPENTRY 
LOGISTICS AND LIGHT INDUSTRY  ESD AREAS

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an **excellent anti-slipping product**.

This sole is called **Kube**, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole.

With thanks to these special characteristics Kube obtained the maximum certification against slipping: **jobs on inclined roofs** (UNI 11583:2015).

**ANTISLIPPING
TEST RESULTS**

request results

SRA

ceramic +	HEEL \geq = 0,28	0,37
NaLS	FLAT \geq = 0,32	0,39

SRB

steel +	HEEL \geq = 0,13	0,20
glycerol	FLAT \geq = 0,18	0,30



SRA+SRB=

SRC

ANTI-SLIPPING SOLE